

Programming Proverbs

- 1. “Define the problem completely”
- 2. “Think first, Program later”
- Henry F. Ledgard, “Programming Proverbs: Principles of Good Programming with Numerous Examples to Improve Programming Style and Proficiency”, (Hayden Computer Programming Series), Hayden Book Company, 1st edition, ISBN-13: 978-0810455221, December 1975.

Know your tools

- “a bad workman blames his tools”,
Cambridge Idioms Dictionary
- we will examine:
 - emacs, etags, grep, diff, patch, gcc, gm2, cvs, gdb, svn
- although in this lecture we will only cover emacs and gdb
 - and revise our knowledge of C pointers

For the GNU/Linux game developer GDB is the BFG

- get to know this tool!


emacs

- GNU Emacs is an extensible, customisable text editor-and more
- at its core is an interpreter for Emacs Lisp, a dialect of the Lisp programming language with extensions to support text editing
- features of GNU Emacs include:
 - content-sensitive editing modes
 - highly customisable, using Emacs Lisp code or a graphical interface
 - can run a shell, ssh session, read news, read mail, run gdb
 - all the above are editing sessions
 - learn how to navigate it once, use it in a multitude of ways

Minimal number of key commands for emacs

- deliberately kept short!
- \hat{c} means control key is pressed and kept down while the `c` key is also pressed. After which both are released.
- `M-x` means press the meta key (the `<alt>` key) and then press the `x` key and then release both.
- `M-x` can also be achieved by pressing the `<esc>` key, releasing it and then pressing `x` and releasing it.
- choose which ever seems most natural

emacs keys



Keys	meaning
=====	
<code>^x^c</code>	exit emacs
<code>^x2</code>	split screens horizontally into two
<code>^xo</code>	move cursor into other window
<code>^x^f</code>	load in a new file
<code>^x^s</code>	save current buffer
<code>^xs</code>	save all buffers
<code>^x`</code>	move to next error
<code>^k</code>	cut rest of line into kill buffer
<code>^y</code>	yank the last kill buffer (paste it into the current location)
<code>^<space></code>	mark the current position
<code>^w</code>	kill all text between current position and last marked position
<code>M-x</code>	move to the execute-extended-command line
<code>^g</code>	stop emacs from doing something
<code>^xb</code>	change buffer (press tab to see all available buffers)

Further emacs information

- [emacs homepage](http://www.gnu.org/software/emacs) `<http://www.gnu.org/software/emacs>`
- the best way to learn how to use emacs is by reading the built-in documentation
- to do this, start emacs and then use the commands:
 - Interactive beginners' tutorial - to start this from within emacs, type `^ht`
 - this is an extremely well written tutorial - well worth the reading effort
 - List of Frequently Asked Questions, type `^h^f`

C Pointers and arrays revisited

- a pointer is a variable that contains an address of a (normally different) variable
- arrays and pointers are closely related in C
- we can declare an array of integers by:

```
int a[10];
```

- and we can declare a pointer to an integer, by:

```
int *b;
```


Initialising a pointer

- we can make b point to the start of the array, by:

- ```
int *b = (int *)&a;
```

- to set the first element of the array to 999 we can either use the pointer or the array variable

## Initialising a pointer

```
#include <stdio.h>

int main ()
{
 int a[10];
 int *b = (int *)&a;

 a[0] = 111;
 printf("the first element of the array has been set to %d\n",
 a[0]);
 *b = 999;
 printf("the value of the first element is now %d\n", a[0]);
 return 0;
}
```

## Initialising a pointer

- we can assign 777 to the second element of the array by the following code:

```
#include <stdio.h>

int main ()
{
 int a[10];
 int *b = (int *)&a;

 b++;
 *b = 777;
 printf("the second element of the array has been set to %d\n",
 a[1]);
 return 0;
}
```

- notice that we moved to the second element on the array by: b++

## Initialising a pointer

- we could have also written the code like this:

```
#include <stdio.h>

int main ()
{
 int a[10];
 int *b = (int *)&a[1];

 *b = 777;
 printf("the second element of the array has been set to %d\n",
 a[1]);
 return 0;
}
```

## Initialising a pointer

■ or like this:

```
■ #include <stdio.h>

int main ()
{
 int a[10];
 int *b = ((int *)&a)+1;

 *b = 777;
 printf("the second element of the array has been set to %d\n",
 a[1]);
 return 0;
}
```

## Initialising a pointer

- the addition of 1 to a pointer means increment the address value in the pointer variable by: `sizeof(*b)` bytes
- avoid arithmetic on pointers if at all possible

## Interchanging pointers and arrays

- we can also set the third element of the array to 444 by:

```
#include <stdio.h>

int main ()
{
 int a[10];
 int *b = (int *)&a;

 b[3] = 444;
 printf("the second element of the array has been set to %d\n",
 b[3]);
 return 0;
}
```

- notice how we are treating b as an array, although we declared it as a pointer

## Interchanging pointers and arrays

- clearer than adding, 3, to a pointer, and the same code is generated by the compiler
- use the debugger to print out values, or set values
- compile the previous example using
- ```
$ gcc -g pointer2.c
```
- then we can run the debugger as follows

Interchanging pointers and arrays

```
$ gdb ./a.out
GNU gdb 6.4.90-debian
Copyright etc...
(gdb) break main
Breakpoint 1 at 0x400480: file pointer2.c, line 6.
(gdb) run
Starting program: /home/gaius/text/Glamorgan/gaius/c/a.out
Breakpoint 1, main () at pointer2.c:6
6      int *b = (int *)&a;
(gdb) step
8      b[3] = 444;
(gdb) ptype b
type = int *
(gdb) step
9      printf("the second element of the array has been set to %d\n",
step
the second element of the array has been set to 444
11 }
```

Interchanging pointers and arrays

```
(gdb) set *b=999
(gdb) print b[0]
$2 = 999
(gdb) print b[3]
$3 = 444
(gdb) set *(b+3)=777
(gdb) print b[3]
$4 = 777
(gdb) quit
```

structs and pointers

- recall a struct can be define a linked list like this:

```
struct list {  
    struct list *right;  
    struct list *left;  
    char        ch;  
}
```

- here we declare a list structure which has 3 fields
 - right, left, and ch
 - right and left are also pointers to a list structure and ch is a character

Initialising a pointer to a struct

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

struct list {
    struct list *right;
    struct list *left;
    char        ch;
};

int main ()
{
    struct list *h = (struct list *)malloc (sizeof (struct list));

    h->right = NULL;
    h->left = NULL;
    h->ch = '\0';

    return 0;
}
```

prototype for malloc

- ```
extern void *malloc (unsigned int nBytes);
```
- which means the function `malloc` takes one parameter, the number of bytes requested
  - and returns an address to the start of a memory block which can be used to contain `nBytes` of information
- remember a generic pointer can be defined by the construct `void *`

# Implementing a program to create a linked list of characters

```
#include <stdlib.h>
#include <stdio.h>
#include <string.h>

const char *myString = "hello world";

struct list {
 struct list *left;
 struct list *right;
 char ch;
};

int main ()
{
 /* unfinished */

 return 0;
}
```

# Implementing a program to create a linked list of characters

- fragment of implementation



```
struct list *head = NULL;

/* need to complete function add */

int main ()
{
 int n = strlen (myString);
 int i;

 for (i=0; i<n; i++) {
 add(a[i]);
 }
 return 0;
}
```



## Implementing function add (which contains one deliberate mistake)

```
void add (char ch)
{
 struct list *e = (struct list *)malloc (sizeof (struct list));
 if (e == NULL) {
 perror("trying to add an element to the list");
 exit(1);
 }
 if (head == NULL) {
 head = e;
 e->right = e;
 e->left = e;
 e->ch = ch;
 }
 else {
 /* add e to the end of the list */
 e->right = head;
 e->left = head->left;
 head->left->right = e;
 head->left = e;
 }
}
```

## Function main

```
int main ()
{
 int n = strlen (myString);
 struct list *f;
 int i;

 for (i=0; i<n; i++) {
 add(myString[i]);
 }
 if (head != NULL) {
 f = head;
 do {
 printf("char %c\n", f->ch);
 f = f->right;
 } while (f != head);
 }
 return 0;
}
```

# Tutorial

- firstly use the debugger and find the bug in `add`
- secondly can you rewrite functions `add` and `main` so that you always keep a dummy head element and therefore you can reduce the `head==NULL` tests
  - the lines of code will reduce and there will be no need for an `else` statement