

emacs customisation (\$HOME/.emacs)

slide 1
gaius

emacs customisation (\$HOME/.emacs)

```
■
;; F5 loads in the .gdbinit file ready for debugging ioquake
(defun my-find-file-debug ()
  "load a file"
  (interactive)
  (find-file (concat (getenv "HOME") "/Sandpit/ioquake-la")
  (global-set-key [f5] 'my-find-file-debug)

;; F12 compiles ioquake
(setq compile-command "make")
(defun my-compile ()
  "run the compile command after moving to the correct directory"
  (interactive)
  (find-file (concat (getenv "HOME") "/Sandpit/ioquake-la")
  (compile compile-command))

;; compile ioquake by pressing
(global-set-key [f12] 'my-compile)

;; F8 moves to the next error in the source file.
(global-set-key [f8] 'next-error)
```

```
■
;; initialise GNU Modula-2 development functions
(load "~/emacs/gm2-emacs")
```

slide 3
gaius

`~/emacs/gm2-emacs`

slide 4
gaius

`~/emacs/gm2-emacs`

```
■
(setq graft-gcc (getenv "GCCVERSION"))

(setq graft-home (concat (concat (concat (concat "/home/gaius/" "src/" "graft"))
  "src/graft")))

(setq build-home (concat (concat (concat (concat "/home/gaius/" "src/" "gm2-emacs"))
  "src/gm2-emacs")))

(setq compile-command "make")

(defun my-compile ()
  "run the compile command"
  (interactive)
  (compile compile-command))

(defun my-find-file-debug ()
  "load a file"
  (interactive)
  (find-file (concat build-home "gcc/.gdbinit"))))
```

```
■
; (add-hook 'after-save-hook 'my-rebuild)

(defun my-rebuild ()
  "rebuild gcc"
  (interactive)
  (let (source-buffer)
    (setq source-buffer (current-buffer))
    (let (gdbinit)
      (delete-other-windows)
      (split-window)
      (other-window 1)
      (my-find-file-debug)
      (compile compile-command)
      (other-window 1)
      (goto-char (point-max))
      (other-window 1)
      (switch-to-buffer source-buffer))))
```

C preprocessor

- the C language is two languages
 - the language which defines data types, statements, functions and operators
 - there is also the language of the preprocessor (#include, #define) etc
- we use #include to include text within the current source file
 - traditionally these text files are .h files or library files, but they can be any text file, including .c files
 - however including .c files is generally considered bad practice
 - however there are exceptions to this rule, for example including machine generated .c files

Example #include

- the following is held in file example.h
 - int example_length (char *s);

Example #include

example.c

- the following is main1.c

```
#include <stdio.h>
#include "example.h"

main ()
{
    printf("my length program counts %d characters\n",
           example_length("hello world"));
}
```

```
■ int example_length (char *s)
{
    int i=0;

    while (s[i] != '\0')
        i++;
    return i;
}
```

#include

- notice that `main1.c` contained two `#includes`, the first was to include the prototype for `printf`
- also notice that it used `<>` to delimit the filename
 - special meaning, it searches using an implementation defined rule to find the file
- you can modify the search path of the `gcc` compiler by supplying the `-I` argument

#include

- you can compile and link these examples into an executable via:

- ```
$ gcc -g example.c main1.c
```

- and run the program via:

- ```
$ ./a.out
```

Macro substitution

- the C preprocessor allows text to be substituted, for example

```
#define forever while (1)
#include <stdio.h>

main ()
{
    forever {
        printf("hello world\n");
    }
}
```

Macro substituted with arguments

- ```
#define assert(X) { if (! (X)) \
 { fprintf(stderr, "assert failed\n" \
 __FILE__ ":" __LINE__); \
 } }
```
- if you are unsure what is happening try asking the preprocessor what it is doing (use `gcc -E`)

## Macro substituted with arguments

```
$ gcc -E main2.c
1 "main2.c"
1 "<built-in>"
1 "<command line>"
1 "main2.c"

main ()
{
 int r = write(1, "hello world\n", 12);

 { if (! (r==12)) { fprintf(stderr, "assert failed\n");
}
```

## Special tokens in the C preprocessor

- `__LINE__`, `__DATE__`, and `__FILE__` are all special tokens and are expanded into their obvious meanings, consider
- the `gcc` C compiler also substitutes `__FUNCTION__` (but it does this in the C language component - not during preprocessing)

- use the C preprocessor carefully...
  - do not use the C preprocessor to gain execution speed (by avoiding a function call)
  - the C compiler will probably make better decisions than you..

## Special tokens in the C preprocessor

`gcc -E main3.c | tail -20`

```
#include <stdio.h>
#include <stdlib.h>
#define assert(X,Y) do_assert(X, Y, __LINE__, __FILE__, __
void do_assert (int b, char *m, int line, char *file,
 const char *func)
{
 if (! b) {
 fprintf(stderr, "%s:%d: %s in function %s (on %s)\n";
 file, line, m, func, __DATE__);
 exit(1);
 }
main ()
{
 int r = write(1, "hello world\n", 11); /* should be 12
 assert(r==12, "write failed");
}
```

```
void do_assert (int b, char *m, int line, char *file,
 const char *func)
{
 if (! b) {
 fprintf(stderr, "%s:%d: %s in function %s (on %s)\n";
 file, line, m, func, "Feb 4 2008");
 exit(1);
 }
main ()
{
 int r = write(1, "hello world\n", 11);
 do_assert(r==12, "write failed", 18, "main3.c", __FUNCTION__);
}
```

## Watch out for side effects

## Correct solution

```
#define square(X) (X)*(X)

main ()
{
 int i=11;
 printf("square of %d is %d\n", i, square(i++));
 printf("square of %d is %d\n", i, square(i++));
```

```
#include <stdio.h>

int square (int x)
{
 return x*x;
}

main ()
{
 int i=11;
 printf("square of 11 is %d\n", square(i++));
 printf("square of 12 is %d\n", square(i++));
```

- why is this wrong?
- never use C preprocessor for speed, unless you know the hardware better than the compiler author..

- and compile with `gcc -O3 -g main4.c` it will produce great code

## Compiler assembler output

## main4.s

- check this is the case!
- compile with `gcc -S -g -O3 main4.c`

```
.LC0:
 .string "square of 11 is %d0
.LC1:
 .string "square of 12 is %d0
.text
main:
 .loc 1 9 0
 subq $8, %rsp
 .loc 1 12 0
 movl $.LC0, %esi
 movl $.LC1, %edi
 xorl %eax, %eax
 call printf
 .loc 1 13 0
 movl $144, %esi
 movl $.LC1, %edi
 xorl %eax, %eax
 .loc 1 14 0
 addq $8, %rsp
 .loc 1 13 0
 jmp printf
```

## C preprocessor conditionals

- C preprocessor allows the following conditionals
  - `#if defined(MACRONAME)`
    - also abbreviated to `#ifdef MACRONAME`
  - first method is preferable as it can be used with conditional logic

## C preprocessor conditionals

```
#define FOO
#define BAR "ok"

#if defined(FOO)
include "myfunc1.h"
#elif defined(BAR) && (BAR == "ok")
include "myfunc2.h"
#else
include "myfunc3.h"
#endif
```

## Revisiting the `example_length`

- goal is to create a prototype header file which allows external access to `example_length`
  - but also allow local prototype checking

## `example2.h`

```
#if !defined(EXAMPLE_H)
define EXAMPLE_H
if defined(EXAMPLE_C)
define EXTERN
else
define EXTERN extern
endif

EXTERN int example_length (char *s);

#endif
```

**example2.c**

```
#define EXAMPLE_C
#include "example2.h"

int example_length (char *s)
{
 int i=0;

 while (s[i] != '\0')
 i++;
 return i;
}
```

**main5.c**

```
#include "example2.h"
#include <stdio.h>

main ()
{
 printf("my length program counts %d characters\n",
 example_length("hello world"));
}
```

**Tutorial****Tutorial**

- extend the `example2` module above to include a function `example_reverse` whose prototype is:

```
char *example_reverse (char *s)
```

- and this function must be implemented to create a new string but copy the contents of, `s`, in reverse order
  - hint you will need to use `malloc`

- extend `main5.c` to test your program

- finally read about the precedence operator `##`
- finally what does the following code do?
  - check the C preprocessor transformation

```
#include <stdio.h>
#define FOO(X) "#X " and this is something extra"
#define DEBUG(X) ("%s:%d:the value of " #X " is %d\n", \
 __FILE__, __LINE__, X)
#define BAR(X,Y) X ## Y

main()
{
 int i=9;
 int fred=3;

 printf(FOO(hi) " to do at the end of the" " lab\n");
 printf DEBUG(i);
 printf("value of fred is %d\n", BAR(fr,ed));
}
```

## Tutorial

- finally write a macro called `check_malloc` which has the same user prototype as `malloc` but checks that the result is non `NULL`
  - and calls `fprintf(stderr, etc,` if the result is `NULL`
- make it as useful as possible