


Moving a along a line

- consider the problem of making a barrels appear to roll across a plank
 - this is complicated by the issue of the ramp gradient



Bresenham's line algorithm


- fortunately Bresenham discovered an algorithm which given two points
 - determines the elements of a 2-dimensional grid that should be selected to best approximate the line
- Bresenham's line algorithm also uses integer arithmetic which adds to its complexity

$$y = mx + c$$

- returning to the problem of making a barrel roll down a plank
 - we know the x position, but we need to compute the y value
- we know the start and end points of the ramp

$$y = mx + c$$

- in the previous slide the start position is (1, 2) and the end position is (5, 4)
 - the dx value is $5-1 = 4$
 - the dy value is $4-2 = 2$
- therefore our gradient m is $\frac{dy}{dx}$



$$\mathbf{y} = \mathbf{mx} + \mathbf{c}$$

$$\mathbf{y} = \mathbf{mx} + \mathbf{c}$$

- we need to calculate c
- we know the point $(1, 2)$ exists on the line
- using $y = mx + c$
- $2 = 1m + c$
- $2 = \frac{1}{2} + c$
- $c = 2 - \frac{1}{2} = 1 + \frac{1}{2}$
- we could use this formula to calculate the y value given an x value
- $m = \frac{2}{4} = \frac{1}{2}$

$$\mathbf{y} = \mathbf{mx} + \mathbf{c}$$

$$\mathbf{y} = \mathbf{mx} + \mathbf{c}$$

- - notice how we need floating point values to compute it
 - also notice how we calculated the gradient
 - Bresenham's algorithm hunts for the correct gradient by using integer arithmetic and by manipulating the numerator and denominator of the fractional value of m
- | x | y |
|---|-----|
| 1 | 2 |
| 2 | 2.5 |
| 3 | 3 |
| 4 | 3.5 |
| 5 | 4 |

Bresenham's algorithm in Python (version 1)

bres0.py

```
#!/usr/bin/env python

def points (p0, p1):
    x0, y0 = p0
    x1, y1 = p1

    dx = abs(x1-x0)
    dy = abs(y1-y0)
    if x0 < x1:
        sx = 1
    else:
        sx = -1

    if y0 < y1:
        sy = 1
    else:
        sy = -1
    err = dx-dy
```

Bresenham's algorithm in Python (version 1)

bres0.py

```
while True:
    print x0, y0
    if x0 == x1 and y0 == y1:
        return

    e2 = 2*err
    if e2 > -dy:
        # overshoot in the y direction
        err = err - dy
        x0 = x0 + sx
    if e2 < dx:
        # overshoot in the x direction
        err = err + dx
    y0 = y0 + sy
```

Bresenham's algorithm in Python (version 1)

Using Bresenham's algorithm to give us the next point

bres0.py

```
# test code
#
points ([1, 2], [5, 4])
```

- we need to change the algorithm very slightly so that we can get the next point on demand
 - really a cosmetic change
- probably best to use a class and a few methods

- when we run this we see:

```
$ python bres0.py
1 2
2 2
3 3
4 3
5 4
```

Python implementation of Bresenham's algorithm (version 2)

Python implementation of Bresenham's algorithm (version 2)

bres1.py

```
#!/usr/bin/env python

class bres:
    def __init__(self, p0, p1):
        self.p0 = p0
        self.p1 = p1
        self.x0 = p0[0]
        self.y0 = p0[1]
        self.x1 = p1[0]
        self.y1 = p1[1]
        self.dx = abs(self.x1-self.x0)
        self.dy = abs(self.y1-self.y0)
```

bres1.py

```
if self.x0 < self.x1:
    self.sx = 1
else:
    self.sx = -1

if self.y0 < self.y1:
    self.sy = 1
else:
    self.sy = -1
self.err = self.dx-self.dy
```

Python implementation of Bresenham's algorithm (version 2)

Python implementation of Bresenham's algorithm (version 2)

bres1.py

```
def get_next (self):
    if self.x0 == self.x1 and self.y0 == self.y1:
        return [self.x1, self.y1]

    self.e2 = 2*self.err
    if self.e2 > -self.dy:
        self.err = self.err - self.dy
        self.x0 = self.x0 + self.sx
    if self.e2 < self.dx:
        self.err = self.err + self.dx
        self.y0 = self.y0 + self.sy
    return [self.x0, self.y0]
```

bres1.py

```
# test code
#
w = bres ([1, 2], [5, 4])
p = w.get_next ()
print p
while p != [5, 4]:
    p = w.get_next ()
    print p
print p
```

Python implementation of Bresenham's algorithm (version 2)

```
$ python bres1.py
[2, 2]
[3, 3]
[4, 3]
[5, 4]
[5, 4]
```

- as can be seen in the test code the use of the Python class is ugly
- we can improve this by introducing a method `finished()` which returns `True` if we have reached the end of the line
- we also note there is a slight bug in version 2 as it omits the initial point!

Python implementation of Bresenham's algorithm (version 3)

Python implementation of Bresenham's algorithm (version 3)

```
bres.py
#!/usr/bin/env python

class bres:
    def __init__(self, p0, p1):
        self.initial = True
        self.end = False
        self.p0 = p0
        self.p1 = p1
        self.x0 = p0[0]
        self.y0 = p0[1]
        self.x1 = p1[0]
        self.y1 = p1[1]
        self.dx = abs(self.x1-self.x0)
        self.dy = abs(self.y1-self.y0)
```

```
bres.py
if self.x0 < self.x1:
    self.sx = 1
else:
    self.sx = -1

if self.y0 < self.y1:
    self.sy = 1
else:
    self.sy = -1
self.err = self.dx-self.dy
```

Python implementation of Bresenham's algorithm (version 3)

Python implementation of Bresenham's algorithm (version 3)

bres.py

```
def get_next (self):
    if self.initial:
        self.initial = False
        return [self.x0, self.y0]

    if self.x0 == self.x1 and self.y0 == self.y1:
        self.end = True
        return [self.x1, self.y1]
```

bres.py

```
self.e2 = 2*self.err
if self.e2 > -self.dy:
    self.err = self.err - self.dy
    self.x0 = self.x0 + self.sx
if self.e2 < self.dx:
    self.err = self.err + self.dx
    self.y0 = self.y0 + self.sy
return [self.x0, self.y0]

def get_current_pos (self):
    return [self.x0, self.y0]

def finished (self):
    return self.end
```

Python implementation of Bresenham's algorithm (version 3)

Test run of our new Python module bres.py

bres.py

```
# test code
#
w = bres ([1, 2], [5, 4])
while not w.finished ():
    p = w.get_next ()
    print p
```

bres.py

```
$ python bres.py
[1, 2]
[2, 2]
[3, 3]
[4, 3]
[5, 4]
[5, 4]
```

Homework and tutorial work

- comment this code
- use this module `bres.py` together with the `explosions.py` code we looked at last week to generate explosions and track the mouse
- declare a `missile` class which can be given two points: `start`, `end` to traverse along a chosen path
- introduce an `update` method for the missile class which moves the missile onto the next coordinate
- tie these pieces together and allow the mouse to fire off a missile from the left, middle, and right silos