

Bresenham's algorithm in Python (version 1)

bres0.py

```
#!/usr/bin/env python3

def points (p0, p1):
    x0, y0 = p0
    x1, y1 = p1

    dx = abs(x1-x0)
    dy = abs(y1-y0)
    if x0 < x1:
        sx = 1
    else:
        sx = -1

    if y0 < y1:
        sy = 1
    else:
        sy = -1
    err = dx-dy
```

Bresenham's algorithm in Python (version 1)

bres0.py

```
while True:
    print (x0, y0)
    if x0 == x1 and y0 == y1:
        return

    e2 = 2*err
    if e2 > -dy:
        # overshoot in the y direction
        err = err - dy
        x0 = x0 + sx
    if e2 < dx:
        # overshoot in the x direction
        err = err + dx
        y0 = y0 + sy
```

Bresenham's algorithm in Python (version 1)

bres0.py

```
#
# test code
#
points ([1, 2], [5, 4])
```

when we run this we see:

```
$ python3 bres0.py
1 2
2 2
3 3
4 3
5 4
```

Using Bresenham's algorithm to give us the next point

- we need to change the algorithm very slightly so that we can get the next point on demand
 - really a cosmetic change
- probably best to use a class and a few methods

Python implementation of Bresenham's algorithm (version 2)

bres1.py

```
#!/usr/bin/env python3

class bres:
    def __init__ (self, p0, p1):
        self.p0 = p0
        self.p1 = p1
        self.x0 = p0[0]
        self.y0 = p0[1]
        self.x1 = p1[0]
        self.y1 = p1[1]
        self.dx = abs(self.x1-self.x0)
        self.dy = abs(self.y1-self.y0)
```

Python implementation of Bresenham's algorithm (version 2)

bres1.py

```
if self.x0 < self.x1:
    self.sx = 1
else:
    self.sx = -1

if self.y0 < self.y1:
    self.sy = 1
else:
    self.sy = -1
self.err = self.dx-self.dy
```

Python implementation of Bresenham's algorithm (version 2)

bres1.py

```
def get_next (self):
    if self.x0 == self.x1 and self.y0 == self.y1:
        return [self.x1, self.y1]

    self.e2 = 2*self.err
    if self.e2 > -self.dy:
        self.err = self.err - self.dy
        self.x0 = self.x0 + self.sx
    if self.e2 < self.dx:
        self.err = self.err + self.dx
        self.y0 = self.y0 + self.sy
    return [self.x0, self.y0]
```

Python implementation of Bresenham's algorithm (version 2)

bres1.py

```
#
# test code
#
w = bres ([1, 2], [5, 4])
p = w.get_next ()
print (p)
while p != [5, 4]:
    p = w.get_next ()
    print (p)
print (p)
```

Python implementation of Bresenham's algorithm (version 2)

```
$ python3 bres1.py
[2, 2]
[3, 3]
[4, 3]
[5, 4]
[5, 4]
```

Tidying up the Python interface

- as can be seen in the test code the use of the Python class is ugly
- we can improve this by introducing a method `finished()` which returns `True` if we have reached the end of the line
- we also note there is a slight bug in version 2 as it omits the initial point!

Python implementation of Bresenham's algorithm (version 3)

Python implementation of Bresenham's algorithm (version 3)

```

bres.py
#!/usr/bin/env python3

class bres:
    def __init__(self, p0, p1):
        self.initial = True
        self.end = False
        self.p0 = p0
        self.p1 = p1
        self.x0 = p0[0]
        self.y0 = p0[1]
        self.x1 = p1[0]
        self.y1 = p1[1]
        self.dx = abs(self.x1-self.x0)
        self.dy = abs(self.y1-self.y0)

```

```

bres.py
        if self.x0 < self.x1:
            self.sx = 1
        else:
            self.sx = -1

        if self.y0 < self.y1:
            self.sy = 1
        else:
            self.sy = -1
        self.err = self.dx-self.dy

```

Python implementation of Bresenham's algorithm (version 3)

bres.py

```
def get_next (self):
    if self.initial:
        self.initial = False
        return [self.x0, self.y0]

    if self.x0 == self.x1 and self.y0 == self.y1:
        self.end = True
        return [self.x1, self.y1]
```

Python implementation of Bresenham's algorithm (version 3)

bres.py

```
self.e2 = 2*self.err
if self.e2 > -self.dy:
    self.err = self.err - self.dy
    self.x0 = self.x0 + self.sx
if self.e2 < self.dx:
    self.err = self.err + self.dx
    self.y0 = self.y0 + self.sy
return [self.x0, self.y0]

def get_current_pos (self):
    return [self.x0, self.y0]

def finished (self):
    return self.end
```

Python implementation of Bresenham's algorithm (version 3)

bres.py

```
#
# test code
#
w = bres ([1, 2], [5, 4])
while not w.finished ():
    p = w.get_next ()
    print (p)
```

Test run of our new Python module bres.py

```
$ python3 bres.py
[1, 2]
[2, 2]
[3, 3]
[4, 3]
[5, 4]
[5, 4]
```